

精密级衰减器>100W

- 型号：A18-Nx-XX-150WG Connector：N 平均功率：150W



Fr. Range (GHz)	Atten & Accuracy (dB)				VSWR (Max)	Material	Size (mm)
	1-10	11-20	21-30	31-40			
DC-8	±0.4	±0.6	±0.8	±1.0	1.20	BeO	200*110*110
DC-12.4					1.25		
DC-18	±0.5	±0.7	±0.8	±1.0	1.30		

- 型号：A18-Nx-XX-200WG Connector：N 平均功率：200W



Fr. Range (GHz)	Atten & Accuracy (dB)				VSWR (Max)	Material	Size (mm)
	1-10	11-20	21-30	31-40			
DC-8	±0.4	±0.6	±0.8	±1.0	1.20	BeO	224*110*110
DC-12.4					1.25		
DC-18	±0.5	±0.7	±0.8	±1.0	1.30		

- 型号：A18-Nx-XX-250WG Connector：N 平均功率：250W



Fr. Range (GHz)	Atten & Accuracy (dB)				VSWR (Max)	Material	Size (mm)
	1-10	11-20	21-30	31-40			
DC-8	±0.4	±0.6	±0.8	±1.0	1.20	BeO	275*110*110
DC-12.4					1.25		
DC-18	±0.5	±0.7	±0.8	±1.0	1.35		

- 型号：A18-Nx-XX-300WG Connector：N 平均功率：300W



Fr. Range (GHz)	Atten & Accuracy (dB)				VSWR (Max)	Material	Size (mm)
	1-10	11-20	21-30	31-40			
DC-8	±0.4	±0.6	±0.8	±1.0	1.20	BeO	299*110*110
DC-12.4					1.35		

- 型号：A18-Nx-XX-500WG Connector：N 平均功率：500W



Fr. Range (GHz)	Atten & Accuracy (dB)				VSWR (Max)	Material	Size (mm)
	1-10	11-20	21-30	31-40			
DC-8	±0.4	±0.6	±0.8	±1.0	1.25	BeO	329*110*110