



Available Variants

TYPE	"L"(mm)	IL. dB@max.		Marking	Weight(g)
		18GHz	26.5GHz		
P49-SfSf-500(T)	500	0.69	0.78	Tuyue YWWZZZ P49-SfSf-500	42.5
P49-SfSf-1000(T)	1000	1.28	1.59	Tuyue YWWZZZ P49-SfSf-1000	75.0
P49-SfSf-2000(T)	2000	2.46	2.98	Tuyue YWWZZZ P49-SfSf-2000	140.0
P49-SfSf-XXXX(T)	XXXX			Tuyue YWWZZZ P49-SfSf-XXXX	

XXXX is cable length and we can follow customer demand. Y - year; ww - Week; zzz - Serial No. .

Assembly Parts

Connector left: SMA-K190G
Connector right: SMA-K190G
Cable: P49

Electrical data

Impedance 50 Ω
Frequency DC to 26.5GHz
VSWR ≤1.20 DC to 18GHz
≤1.25 DC to 26.5GHz
Insertion loss See table available variants
RF-leakage ≥ 100 dB up to 1 GHz

Mechanical data

Minimum Bend Radius
Single: 12.5 mm
Multiple: 38.1 mm
Jacket Diameter: 4.8 mm

Environmental data

Temperature range -55°C to +165°C
2002/95/EC (RoHS) compliant