



Available Variants

TYPE	"L"(mm)	IL. dB@max 18GHz	Marking	Weight(g)
BLU18A-NfNf-500(T)	500	0.79	Tuyue YWWZZZ BLU18A-NfNf-500	114
BLU18A-NfNf-1000(T)	1000	1.28	Tuyue YWWZZZ BLU18A-NfNf-1000	150
BLU18A-NfNf-2000(T)	2000	2.46	Tuyue YWWZZZ BLU18A-NfNf-2000	222
BLU18A-NfNf-XXXX(T)	XXXX		Tuyue YWWZZZ BLU18A-NfNf-XXXX	

XXXX is cable length and we can follow customer demand. Y - year; ww - Week; zzz - Serial No. .

Assembly Parts

Connector left: N-K210G
Connector right: N-K210G
Cable:210A

Electrical data

Impedance 50 Ω
Frequency DC to 18GHz
VSWR ≤ 1.25 DC to 18GHz
Insertion loss See table available variants
RF-leakage ≥ 100 dB up to 1 GHz

Mechanical data

Minimum Bend Radius
Single: 12.5 mm
Multiple: 38.1 mm
Jacket Diameter: 5.5 mm

Environmental data

Temperature range -55°C to +125°C
2002/95/EC (RoHS) compliant