



#### Available Variants

TYPE	"L"(mm)	IL. dB@max.		Marking	Weight(g)
		18GHz	26.5GHz		
P07-SfSf-500	500	1.27	1.48	Tuyue YWWZZZ P07-SfSf-500	26.5
P07-SfSf-1000	1000	2.08	2.59	Tuyue YWWZZZ P07-SfSf-1000	43.0
P07-SfSf-2000	2000	3.89	4.88	Tuyue YWWZZZ P07-SfSf-2000	76.0
P07-SfSf-XXXX	XXXX			Tuyue YWWZZZ P07-SfSf-XXXX	

**XXXX** is cable length and we can follow customer demand. Y - year; ww - Week; zzz - Serial No. .

#### Assembly Parts

Connector left: SMA-K07G  
Connector right: SMA-K07G  
Cable: P07

#### Electrical data

Impedance	50 $\Omega$
Frequency	DC to 26.5GHz
VSWR	$\leq 1.30$ DC to 18GHz $\leq 1.35$ DC to 26.5GHz
Insertion loss	See table available variants
RF-leakage	$\geq 100$ dB up to 1 GHz

#### Mechanical data

Minimum Bend Radius  
Single: 9.65 mm  
Multiple: 38.6 mm  
Jacket Diameter: 3.6 mm

#### Environmental data

Temperature range	-55°C to +125°C
2002/95/EC (RoHS)	compliant