



Available Variants

TYPE	"L"(mm)	IL. dB@max		Marking	Weight(g)
		18GHz	26.5GHz		
BLU26A-35m35m-500	500	0.79	1.02	Tuyue YWWZZZ BLU26A-35m35m-500	46
BLU26A-35m35m-1000	1000	1.38	1.76	Tuyue YWWZZZ BLU26A-35m35m-1000	82
BLU26A-35m35m-2000	2000	2.76	3.49	Tuyue YWWZZZ BLU26A-35m35m-2000	154
BLU26A-35m35m-XXXX	XXXX			Tuyue YWWZZZ BLU26A-35m35m-XXXX	

XXXX is cable length and we can follow customer demand. Y - year; ww - Week; zzz - Serial No. .

Assembly Parts

Connector left: 3.5mm-J210G
Connector right: 3.5mm-J210G
Cable:210A

Electrical data

Impedance 50 Ω
Frequency DC to 26.5GHz
VSWR ≤1.30, DC to 26.5GHz
Insertion loss See table available variants
RF-leakage ≥ 100 dB up to 1 GHz

Mechanical data

Minimum Bend Radius
Single: 12.5 mm
Multiple: 38.1 mm
Jacket Diameter: 5.5 mm

Environmental data

Temperature range -55°C to +125°C
2002/95/EC (RoHS) compliant